

power tool accessories

1 RCD3

RCD Adaptor

Tested to BS 1363 and IEC 61540

For use in domestic and industrial premises where RCD protection is required. Has reset and test facility. Can be plugged into standard 13A socket. Display packed.

Specification:

Rated voltage	... 230 - 250V/AC
Load	... 3120W (max.)
Maximum operating current	... 13A
Rated trip current	... 30mA
Trip speed	... 30mS (typical)
Double pole RCD contact break.	

Stock No.	Box Qty	Price each
69307	-	€25.37D



2 RCD4

In Line RCD

Tested to BS 1363 and IEC 61540

RCD that is wired between the appliance and mains plug. For use on industrial and domestic products especially where rough handling is expected. Ideal for garden power products. Has reset and test light facility. Display packed.

Specification:

Rated voltage	... 230 - 250V/AC
Load	... 3840W (max.)
Maximum operating current	... 16A
Rated trip current	... 30mA
Trip speed	... 30mS (typical)
Protection class	... IP55.

Stock No.	Box Qty	Price each
89301	-	€43.01D



DAVE SAYS

RCD PROTECTION -

When using devices inside and out it is essential that they are connected to the electrical supply through an RCD.

Essentially the RCD detects when the electric current is not balanced between the phase and neutral conductors. Such an imbalance is sometimes caused by current leakage through the body of the person who is on the ground and accidentally touching the energised part of the circuit. A lethal shock can ensue from these conditions. RCD's are designed to disconnect the supply quickly to avoid this happening.



QUALITY MAKES THE DIFFERENCE

3 MT3

Pack of Three 230V 24 Hour Mechanical Timers

48 on/off settings per 24 hours. Minimum setting time 30 minutes. Manual override switch. Rated 8A/2000W. Correctly used this timer can save the user energy and money. Display packed in threes.

Order number of packs required. (3 per pack)

Stock No.	Box Qty	Price p/pack
44914	12	€16.51D



4 DT2

Pack of Two 230V 7 Day Digital Timers

140 programmable on/off settings per week, countdown and random functions. AM, PM or 24 hour settings. Battery back up. Rated 8A/2000W. Correctly used this timer can save the user energy and money. Display packed in twos.

Order number of packs required. (2 per pack)

Stock No.	Box Qty	Price p/pack
44912	12	€25.56D



5 TPE

Pack of Two European Travel Adaptors

Conforms to BS5733

Allows UK and ROI three pin plugs to be used in European round pin two-pin sockets. Maximum current 10A. Packed two per display card.

Order number of cards required. (2 per card)

Stock No.	Box Qty	Price per card
90061	10	€8.06D



6 TPW

Pack of Two Worldwide Travel Adaptors

Conforms to BS5733

Allows UK and ROI three pin plugs to be used in European and worldwide flat pin two-pin sockets. Pins twist to vertical or 'V' shaped configuration. Maximum current 10A. Packed two per display card.

Order number of cards required. (2 per card)

Stock No.	Box Qty	Price per card
90069	10	€5.69D



extension leads

7 ES4/1A

4-Way Extension Lead (13A)

Manufactured to BS1363 Specifications and BSI Approved

This slimline design is suitable for use with all household appliances including computers and peripherals up to and including 13A. Fitted with 1M (approx.) of cable and 13A fused three pin plug. Packed in polythene bag with header card.

Stock No.	Box Qty	Price each
72716	-	€9.98D



8 ES5/2ASTA

5 Way Anti-Surge Extension Lead with Telephone/Modem Ports

Complies with BS5733, EN60950:1992 and IEC61643:1998 Specifications. BSI Approved

Suitable for use with all household appliances especially computers and peripherals up to a total of 13A (3120W). The anti-surge feature helps to avoid current 'spikes' damaging computers and delicate measuring equipment etc. Special ports allow connections to the telephone and internet to be protected. Surge protection enabled shown by built-in neon indicator. Supplied with 2M (approx.) telephone connection lead. Fitted with 2M (approx.) of cable and 13A fused three pin plug. Display packed.

Stock No.	Box Qty	Price each
72717	-	€36.53D

