low noise compressors

PAUL SAYS

These special Low Noise Compressors (Item Nos. 1 and 2 this page and No. 1 opposite) are ideal for use in environments where noise is an issue. Workshops in garages, schools etc. where the noise level needs to be kept to a minimum but work still needs to be carried out. The typical reduction is up to 24% less noise pressure of an equivalent compressor.

QUALITY ASSURANCE MAKES THE DIFFERENCE

1 DA50/260S

50L 230V 1.8kW Low Noise Air Compressor

Features:

• ***Expert Quality*** • 1.8kW (2.5HP) • Soundproof box over motor • Sound pressure level only 73dBA - compared to an average of 93dB(A) for an unprotected motor • Power and portability • Pressure switch, pressure regulator and pressure gauge • Wheels and transport handle • Carton packed on pallet

Specification:

Air displacement	... 9.2cfm (260L/min)
Free air delivered (FAD)	... 5.3cfm (150L/min)
Input Current	... 13A
Speed	... 2850r/min
Sound pressure level	... 73dB(A)
Maximum pressure	... 145psi (10bar)
Number of cylinders	... 1
Dimensions	... 1000 x 390 x 760mm
Weight	... 50kg

Stock No.	Box Qty	Price each
05640	–	€1402.87P

2 DA90/310S

90L 230V 2.2kW V-Twin Low Noise Air Compressor

Features:

• ***Expert Quality*** • 2.2kW (3.0HP) • Soundproof box over motor • Sound pressure level only 69dB(A) - compared to an average of 93dB(A) for an unprotected motor • V-twin-cylinder cast iron pump • Power and portability • Pressure switch, pressure regulator and pressure gauge • Wheels and transport handle • Carton packed on pallet

Specification:

Air displacement	... 11cfm (310L/min)
Free air delivered (FAD)	... 6.8cfm (192L/min)
Input Current	... 13A
Speed	... 1420r/min
Sound pressure level	... 69dB(A)
Maximum pressure	... 145psi (10bar)
Number of cylinders	... 1
Dimensions	... 1150 x 480 x 885mm
Weight	... 88kg

Stock No.	Box Qty	Price each
05641	–	€2422.56P

3

Compressor Oil

Blended amber coloured oil using a high VI premium grade base oil and selective additives to provide long term protection and reliability for compressors. Suitable for single and multi-stage compressors up to temperatures of 200°C. Display packed.

Specification:

ISO VG Grade	... 46
Density at 15°C	... 0.871
Viscosity at 40°C	... 46.1
Viscosity at 100°C	... 7.0
Viscosity index	... 108

Stock No.	Part No.	Volume	Box Qty	Price each
34683	CO1000	1L	–	€12.58D
34684	CO5000	5L	–	€47.04D

Prices are list, each and exclude VAT.