

1 DA50/260S
50L 230V 1.8kW Low Noise Air Compressor

Features:
 • **Expert Quality** • 1.8kW (2.5HP) • Soundproof box over motor • Sound pressure level only 73dB(A) - compared to an average of 93dB(A) for an unprotected motor • Power and portability • Pressure switch, pressure regulator and pressure gauge • Wheels and transport handle • Carton packed on pallet

Specification:
 Air displacement ... 9.2cfm (260L/min)
 Free air delivered (FAD) ... 5.3cfm (150L/min)
 Input Current ... 13A
 Speed ... 2850r/min
 Sound pressure level ... 73dB(A)
 Maximum pressure ... 145psi (10bar)
 Number of cylinders ... 1
 Dimensions ... 1000 x 390 x 760mm
 Weight ... 50kg

Stock No.	Box Qty	Price each
05640	-	£1169.06P

2 DA90/310S
90L 230V 2.2kW V-Twin Low Noise Air Compressor

Features:
 • **Expert Quality** • 2.2kW (3.0HP) • Soundproof box over motor • Sound pressure level only 69dB(A) - compared to an average of 93dB(A) for an unprotected motor • V-twin-cylinder cast iron pump • Power and portability • Pressure switch, pressure regulator and pressure gauge • Wheels and transport handle • Carton packed on pallet

Specification:
 Air displacement ... 11cfm (310L/min)
 Free air delivered (FAD) ... 6.8cfm (192L/min)
 Input Current ... 13A
 Speed ... 1420r/min
 Sound pressure level ... 69dB(A)
 Maximum pressure ... 145psi (10bar)
 Number of cylinders ... 1
 Dimensions ... 1150 x 480 x 885mm
 Weight ... 88kg

Stock No.	Box Qty	Price each
05641	-	£2018.80P

low noise compressors

PAUL SAYS

These special Low Noise Compressors (Item Nos. 1 and 2 this page and No. 1 opposite) are ideal for use in environments where noise is an issue. Workshops in garages, schools etc. where the noise level needs to be kept to a minimum but work still needs to be carried out. The typical reduction is up to 24% less noise pressure of an equivalent compressor.



3
Compressor Oil

Blended amber coloured oil using a high VI premium grade base oil and selective additives to provide long term protection and reliability for compressors. Suitable for single and multi-stage compressors up to temperatures of 200°C. Display packed.

Specification:
 ISO VG Grade ... 46
 Density at 15°C ... 0.871
 Viscosity at 40°C ... 46.1
 Viscosity at 100°C ... 7.0
 Viscosity index ... 108

Stock No.	Part No.	Volume	Box Qty	Price each
34683	CO1000	1L	-	£10.48D
34684	CO5000	5L	-	£39.20D